Appl. No.

: 10/758,495

Filed

: January 15, 2004

## **AMENDMENTS TO THE CLAIMS**

1. - 54. (Canceled)

55. (Currently amended) A sensor for implantation within a blood vessel comprising:

a support structure;

a sensor housing carried by the support structure; and

a sensing surface exposed to the exterior of the housing;

wherein the sensor is configured to detect nitric oxide or a <u>metabolic</u> <u>product of nitric oxide—metabolite</u>, and wherein the sensor has streamlined configuration with respect to the support-, and wherein the sensing surface <u>includes a layer that minimizes the formation of thrombus.</u>

- 56. (Previously presented) An implantable sensor as in Claim 55, wherein the support structure comprises a stent.
- 57. (Previously presented) An implantable sensor as in Claim 55, wherein the support structure comprises a catheter.
- 58. (Previously presented) An implantable sensor as in Claim 55, wherein the support structure comprises an expandable metal mesh.
- 59. (Previously presented) An implantable sensor as in Claim 55, wherein the sensor housing is positioned on the luminal side of the support structure.
- 60. (Previously presented) An implantable sensor as in Claim 55, wherein the sensor housing is positioned within an opening on the side wall of the support structure.
- 61. (Previously presented) An implantable sensor as in Claim 55, further comprising a tubular sleeve surrounding the support structure.
- 62. (Previously presented) An implantable sensor as in Claim 61, wherein the tubular sleeve is on the radially outwardly facing surface of the support structure.
- 63. (Previously presented) An implantable sensor as in Claim 61, wherein the tubular sleeve comprises ePTFE.
- 64. (Previously presented) An implantable sensor as in Claim 55, wherein the sensor comprises an ion-selective electrode.

Appl. No.

: 10/758,495

:

**Filed** 

January 15, 2004

65. (Previously presented) An implantable sensor as in Claim 55, wherein the sensor is selected from the group consisting of amperometric electrodes, porphyrinic electrodes, and microchip electrodes.

- 66. (Previously presented) An implantable sensor as in Claim 55, further containing an analyte permeable membrane and an enzyme gel layer.
- 67. (Previously presented) An implantable sensor as in Claim 66, wherein the enzyme gel layer comprises nitrate reductase.
- 68. (Currently amended) A sensor for implantation within a blood vessel comprising:
  - a support structure;
  - a sensor housing carried by the support structure; and
- a sensing surface exposed to the exterior of the housing and wherein the sensing surface includes a layer that minimizes the formation of thrombus;

wherein the sensor is configured to detect a <u>metabolic product of nitric</u> oxide <u>metabolite</u>.

- 69. (Previously presented) An implantable sensor as in Claim 68, wherein the support structure comprises a stent.
- 70. (Previously presented) An implantable sensor as in Claim 68, wherein the support structure comprises a catheter.
- 71. (Previously presented) An implantable sensor as in Claim 68, wherein the support structure comprises an expandable metal mesh.
- 72. (Previously presented) An implantable sensor as in Claim 68, wherein the sensor housing is positioned on the luminal side of the support structure.
- 73. (Previously presented) An implantable sensor as in Claim 68, wherein the sensor housing is positioned within an opening on the side wall of the support structure.
- 74. (Previously presented) An implantable sensor as in Claim 68, further comprising a tubular sleeve surrounding the support structure.
- 75. (Previously presented) An implantable sensor as in Claim 74, wherein the tubular sleeve is on the radially outwardly facing surface of the support structure.

Appl. No.

10/758,495

**Filed** 

: January 15, 2004

76. (Previously presented) An implantable sensor as in Claim 74, wherein the tubular sleeve comprises ePTFE.

- 77. (Previously presented) An implantable sensor as in Claim 68, wherein the sensor comprises an ion-selective electrode.
- 78. (Previously presented) An implantable sensor as in Claim 68, wherein the sensor is selected from the group consisting of amperometric electrodes, porphyrinic electrodes, and microchip electrodes.
- 79. (Previously presented) An implantable sensor as in Claim 68, further containing an analyte permeable membrane and an enzyme gel layer.
- 80. (Previously presented) An implantable sensor as in Claim 79, wherein the enzyme gel layer comprises nitrate reductase.